

SHELL CALLINA® Fluid 1210

Maintenance and floor cleaner

SHELL CALLINA® Fluid 1210 is a general maintenance and floor cleaner that provides excellent performance in a variety of general maintenance applications.

Performance Features and Benefits

- Effectively removes a variety of soils such as machining fluids, grease, rubber tire marks, crayon to produce a suitable clean surface.
- Works well for a variety of applications minimizing the need for a variety of products helping to reduce inventory

Main Applications

- Floor cleaning
- Spray cleaning of floors, walls, equipment and machinery
- Floor scrubbing equipment

Advice on applications not covered in this handbook may be obtained from your Shell representative.

Normal Use Conditions

- Floor Cleaning - mop and bucket 3 – 10% concentration, cold or hot, as desired.
- Spray Cleaning - use at 3 – 10% concentration, cold or hot, as desired.

Typical Physical Properties

| SHELL CALLINA® Fluid 1210 | Test Method | |
|---------------------------|-------------|----------------|
| Appearance of Concentrate | Visual | Aqua/ Lt. Blue |
| Odor | | Mild |
| Foam Characteristics | | Low |
| pH Concentrate | | 9.5 |
| Density, lbs per gallon | | 8.7 |

These characteristics are typical of current production. While future production will conform to Shell specifications, variation in these characteristics may occur.

NOTE: SHELL CALLINA® Fluid 1210 contains little corrosion inhibiting ability so bare metal surfaces should be coated with a light oil or coolant solution after cleaning to prevent corrosion from occurring.

Handling and Safety Information

For information on the safe handling, storage, or use of this product, refer to its Material Safety Data Sheet at <http://www.epc.shell.com/>. If you are a Shell Distributor, please call 1+800-332-6457 for all of your service needs. All other customers please call 1+800-237-8645 for all of your service needs.

Protect the Environment

Do not discharge into drains, soil, or water.