



# SHELL RETINAX<sup>®</sup> GREASE EPX 2

## Multipurpose lithium grease with moly

---

### Product Description

Shell Retinax<sup>®</sup> Grease EPX 2 (formerly Retinax<sup>®</sup> Grease AM) grease is a multipurpose lithium soap grease that contains molybdenum disulfide. It has a good dropping point, good mechanical stability, rust inhibition, and water resistance.

### Applications

- heavy loads
- off-highway
- over-the-road
- industrial equipment

### Features/Benefits

- 3% molybdenum disulfide for enhanced EP performance
- corrosion protection in salt water
- rust-inhibition
- water resistance
- application temperatures extending to 275°F(135°C)
- non-lead

### Approvals and Recommendations

- Meets AAR M-929 lubricant specification for trailer hitch on cars

---

#### Typical Properties of Shell Retinax<sup>®</sup> Grease EPX 2

	Test Method	
Product Code		71119
NLGI Grade		2
Base Oil Viscosity:		
@ 40°C, cSt	D 445	200
@ 100°C, cSt	D 445	17.2
Rust Prevention Rating (5% sea water)	D 1743	1
Dropping Point, (°F)	D 2265	385
Worked Penetration, dmm @ 77°F	D 217	275
Molybdenum Disulfide, wt%		3
Timken OK Load, lbs	D 2509	50

### Handling and Safety Information

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet at <http://www.shell-lubricants.com/msds/>. If you are a Shell Distributor, please call 1+800-468-6457 for all of your service needs. All other customers, please call 1+800-840-5737 for all of your service needs. Information is also available on the World Wide Web: <http://www.shell-lubricants.com/>.