



PRODUCT SPECIFICATIONS & TECHNICAL DATA

MULTI-PURPOSE MP-2 GREASE

PREMIUM MULTI-PURPOSE MP-2 GREASE is versatile multi-purpose grease that can be used over a wide temperature range and under varied operating conditions. It functions well in all kinds of climate and weather. It is manufactured from a blend of select petroleum base oils and thoroughly chosen lithium soap.

PREMIUM MULTI-PURPOSE MP-2 GREASE maintains a strong adhesive and cohesive film of lubricating protection on any metal surface.

BENEFITS:

- Water resistance - protects sensitive bearings and metal parts against water washouts
- Heat resistance - does not melt away and therefore, longer protection is assured
- Pumpability - dispenses easily especially in cold weather
- Mechanical stability - does not fall apart when subjected to mechanical agitation

APPLICATION:

General chassis grease for automobiles, trucks, tractors, buses, earth moving equipment, and general industrial machinery.

TYPICAL PROPERTIES

NLGI Grade	2
Texture	Buttery
Thickening Agent	Lithium
Color	Amber
Consistency Worked	
Penetration @ 77° F	265-295
Dropping Point °F Min.	389
Viscosity of Mineral Oil	675
SUS @ 100° F	
Timken OK Load lbs.	40
Rust Protection	PASS
Viscosity Index	93
Oxidation Stability	Excellent

These characteristics are typical of current production

Minor variations that do not affect product performance are to be expected during normal manufacture.

Due to continual product research and development the product formulations are subject to change without notifications.



PRIVATE
LABELS